



CFA200 SLC CFast Memory

The full speed of the SATA interface is available with the CFast memory card for powerful controllers. Up to 30x the transmission rates of the CF cards can be reached. Given the high availability demands placed on automation systems, program and data memory must be selected with particular care. The CFast memory cards CFA200 are therefore especially selected industrial types that can cope with the requirements of harsh daily working routines.

Use of the CFA200 both in CPUs of the M1 family as well as in our visualization devices is strongly recommended due to the extreme environmental conditions, the large number of supported write cycles and the many years of lasting experience with suppliers. The robustness was significantly increased in comparison with a CF card via a stable edge connector.

- CFast type I
- Memory capacity 4 / 8 / 16 GB
- Fast data transfer
- Write protection via software
- Extended temperature range
- Long service life / MTTF

Item	Item-No.
CFA200/4GB	00017355-00
CFA200/8GB	00021781-00
CFA200/16GB	00019082-00

CFA200 SLC	
Technical data	
Memory type	CFast type I
Memory capacity	4 / 8 / 16 GB
Data transfer rate	Up to 300 MB/s
NAND flash type	SLC
Operating voltage	3.3
Read / write cycles	> 60,000
MTBF at 25 °C	> 2,000,000 h (depending on free memory)
Vibration	15 G 10 Hz to 2 kHz
Shock	1500 G half cycle 0.5 ms
Ambient conditions	
Operating temperature	-40 to +85 °C
Rel. humidity operation	5 to 95 % without condensation
Storage temperature	-40 to +85 °C
Rel. humidity storage	5 to 95 % without condensation

Order codes CFA200 SLC		
Item	Item no.	Description
CFA200/4GB	00017355-00	CFast Card 4 GB
CFA200/8GB	00021781-00	CFast Card 8 GB
CFA200/16GB	00019082-00	CFast Card 16 GB